

Iris LED surface-mounted wall luminaire, direct beam

Design
M. Kocks, P. H. Neuhorst

IRIS-W-D-LED 2040-840-T



Direct beam ring-shaped luminaire made of highly transparent plastic. The rotationally symmetrical, flame retardant and impact resistant luminaire housing is slightly offset from the wall. Glare reduction by means of round diffuser panel made of highly transparent plastic with microprism structure which clips in from the front. Central round white powder-coated steel panel to cover the gear tray and for wall mounting. All metal parts are powder coated. Wall luminaire with heat-resistant wiring. Colour: housing – transparent; ceiling box similar to RAL 9016 White silk matt. Colour accentuation of the housing possible by inserting a separately available colour inlay film. LED: 3 LED ring segment boards for indirect lighting component.

Safety class I

Protection rating IP20

Lamps	Ballast	Prod. code
3xLED-M 4W	LED Driver	SPI0000050AY

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
1048	14	74



Dimens. [mm]			Weight [kg]	Photometric data		
H	D			Longitudinal UGR	Transverse UGR	LOR
59	363		2,5	15.5	15.4	99.8 %

Iris
LED surface-mounted wall luminaire,
direct beam

