



## Iris LED surface-mounted ceiling luminaire, direct beam

Design  
M. Kocks, P. H. Neuhorst



### IRIS-A-D-LED 1950-830-T DALI

Direct beam ring-shaped luminaire made of highly transparent plastic. The rotationally symmetrical, flame retardant and impact resistant luminaire housing is slightly offset from the ceiling. Transparent insect protection ring separately available as an accessory. Glare reduction by means of round diffuser panel made of highly transparent plastic with microprism structure which clips in from below. Central round white powder-coated steel panel to cover the gear tray and for ceiling mounting. Ceiling luminaire with heat-resistant wiring. All metal parts are powder coated. Colour: housing - transparent; ceiling box - similar to RAL 9016 white silk matt. Colour accentuation of the housing possible by inserting a separately available colour inlay film. LED: 3 LED ring segment boards for direct lighting component. Light colours 830, 840.

Safety class I  
Protection rating IP20

Lamps	Ballast	Prod. code
3xLED-M 4W	LED Driver DALI	SPI0000049AY

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
1722	16	107



Dimens. [mm]			Weight [kg]	Photometric data		
H	D			Longitudinal UGR	Transverse UGR	LOR
79	363		2,5	17,5	17,4	88,3 %

EEC A++ - A  
Energy efficiency class scale A++ - E

**Iris**  
**LED surface-mounted ceiling luminaire,**  
**direct beam**

