



Norea Round LED pendant lamp small

Design
P. H. Neuhorst

NOREA-RP 306/1900/840 OS

Round element with an opal acrylic panel in a natural anodised aluminium profile frame surround. The frame is fixed at the powder-coated metal body by a bayonet fixture with spring clip. The luminaire is suspended by a six trapezoidal wire pendants with ceiling fixture and transparent connecting cable round ceiling junction box. Cable length adjustable at the junction box, steel wire steplessly height adjustable. The metal body accommodates the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. Luminaire with heat-resistant wiring. Homogenous illumination of the light surface. Suitable for ceiling or wall mounting. Also in a dimmable version.



Colour:

Housing - similar to RAL 9016 White silk matt;

Frame - natural anodised

Lamps	Ballast	Prod. code
1xLED-M 10 W	LED Driver	SPT0000129

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
1284	15	85



Dimens. [mm]			Weight [kg]	Photometric data		
L	B	H		Longitudinal UGR	Transverse UGR	LOR
306	306	78	3,2	25.1	24.5	67.6 %

Norea
Round LED pendant lamp small

