



## Norea Round LED pendant lamp MPS large

Design  
P. H. Neuhorst

### NOREA-RP 416/4300/840 MPS

Round luminaire element with a microprism panel in a natural anodised aluminium profile frame surround. The frame is fixed at the powder-coated metal body by a bayonet fixture with spring clip. The luminaire is suspended by a six trapezoidal wire pendants with ceiling fixture and transparent connecting cable round ceiling junction box. Cable length adjustable at the junction box, steel wire steplessly height adjustable. The metal body accommodates the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. Luminaire with heat-resistant wiring. Variant suitable for office use with a microprism panel MPS. The LED points are visible as circles on the microprism panel. Also in a dimmable version.

Protection rating IP20, safety class I.



Colour:

Housing – similar to RAL 9016 White silk matt;

Frame – natural anodised

Lamps	Ballast	Prod. code
1xLED-M 27 W	LED Driver	SPT0000138

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
3162	31	102



Dimens. [mm]			Weight [kg]	Photometric data		
L	B	H		Longitudinal UGR	Transverse UGR	LOR
416	416	78	4,8	19,8	19,3	62,0 %

**Norea**  
**Round LED pendant lamp MPS large**

