Spectral®



Norea Round LED surface-mounted ceiling luminaire MPS small

Design P. H. Neuhorst

NOREA-RA 306/1900/840 MPS

Round luminaire element with a microprism panel in a natural anodised aluminium profile frame surround. The frame is fixed at the powder-coated metal body by a bayonet fixture with spring clip. The metal body accommodates the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. Luminaire with heat-resistant wiring. Variant suitable for office use with a microprism panel MPS. The LED points are visible as circles on the microprism panel. Suitable for ceiling or wall mounting. Also in a dimmable version.

Protection rating IP20, safety class I Colour:

Housing – similar to RAL 9016 White silk matt; Frame – natural anodised

Lamps		Ballast			Prod. code SPT0000146			
1xLED-M 10 W		LED Driv	/er					
Luminaire lum flux [lm]	nous	Luminaire output [W]		Lumina [lm/W	ire efficiency]			
1178			15	78				
	Ø306 Ø288					90° 75° 60° 45° 30° I (cd/klm)	90° 90° 100 150 200 250 300 0° 45° 30° 30°	
Dimens. [mm			Weight		Photometric data			
L	В	н	[kg]		Longitudinal UGR	TransverseUGR	LOR	
306	306	78	3,2		18.5	18.0	62.0 %	

Spectral®

Norea Round LED surface-mounted ceiling luminaire MPS small

