

Similar photo

Orto ORTO-S ... SR-NM-FSW

ORTO-S 8500-840 SR-NM-FSW

Floor-standing luminaire with direct-indirect beam, luminaire head in extruded aluminium, arranged longitudinally to the stand with precision 90° die-cast component, black (...-FSW, similar to RAL9005), powder coated. Corner connector and stand adapter in brushed matte nickel. Pre-fitted cell-shaped louvre SR in black polycarbonate for optical control of direct light distribution. Optical controllers indirect through cover, clear panel. Stand in extruded aluminium with closed cross-section for optimum stability. Black stand foot in fine-grained black steel. Black mains cable with Schuko plug, 3 m in length. Touchpanel for switching and dimming installed in the stand and integrated USB charging station. Mid-power LED modules for maximum lighting efficiency. Colour rendering in index Ra > 80, colour temperature 4000 Kelvin (-840). Protection class I, protection rating IP20. Non-standard designs with smooth, polished powder coating, only available in combination with matte brushed nickel or polished chrome corner connector, end cap and stand adapter.

Lamps


1xLED 33 W / 1xLED 40 W

Ballast

LED Driver DALI

Prod. code

SPG0630023AQ



Dimens. [mm]			Weight [kg]			
L	B	H				
1314	350	2142	23,0			

EEC A++ - A

Energy efficiency class scale A++ - E

Orto
ORTO-S ... SR-NM-FSW