

Similar photo

## Orto ORTO-T ... SR

### ORTO-T 8500-840 SR

Tablelamp with direct-indirect beam, luminaire head in extruded aluminium, arranged longitudinally to the stand with precision 90° die-cast component, white (similar to RAL9016), powder-coated.

Pre-fitted cell-shaped louvre SR in black polycarbonate for optical control of direct light distribution. Optical controllers indirect through cover, clear panel. Mounted on table using clamp stand; clamp width: 15 mm to 40 mm.

Black mains cable with Schuko plug, 3 m in length. Touchpanel for switching and dimming installed in the stand and integrated USB charging station.

Mid-power LED modules for maximum lighting efficiency.

Colour rendering in index Ra > 80, colour temperature 4000 Kelvin (-840).

Protection class I, protection rating IP20.

Non-standard designs with smooth, polished powder coating, only available in combination with matte brushed nickel or polished chrome corner connector, end cap and stand adapter.

#### Lamps


1xLED 33 W / 1xLED 40 W

#### Ballast

LED Driver DALI

#### Prod. code

SPG0630025AH



Dimens. [mm]			Weight [kg]				
L	B	H					
1314	62	1460	7,3				

#### EEC A++ - A

Energy efficiency class scale A++ - E

Orto  
ORTO-T ... SR