

Similar photo

## Orto ORTO-T ... SR-NM-FSW-SEN

### ORTO-T 8500-840 SR-NM-FSW-SEN

Tablelamp with direct-indirect beam, luminaire head in extruded aluminium, arranged longitudinally to the stand with precision 90° die-cast component, black (...-FSW, similar to RAL9005), powder-coated. Corner connector and stand adapter in brushed matte nickel.

Pre-fitted cell-shaped louvre SR in black polycarbonate for optical control of direct light distribution. Optical controllers indirect through cover, clear panel. Mounted on table using clamp stand; clamp width: 15 mm to 40 mm.

Black mains cable with Schuko plug, 3 m in length. Touchpanel for switching and dimming installed in the stand and integrated USB charging station.

Model with sensor for movement-dependent switching and daylight-dependent dimming.


Mid-power LED modules for maximum lighting efficiency.

Colour rendering in index Ra > 80, colour temperature 4000 Kelvin (-840).

Protection class I, protection rating IP20.

Non-standard designs with smooth, polished powder coating, only available in combination with matte brushed nickel or polished chrome corner connector, end cap and stand adapter.

Lamps	Ballast	Prod. code
1xLED 33 W / 1xLED 40 W	LED Driver DALI	SPG0630028AQ



Dimens. [mm]			Weight [kg]
L	B	H	
1400	62	1460	7,3

EEC A++ - A

Energy efficiency class scale A++ - E

**Orto**  
**ORTO-T ... SR-NM-FSW-SEN**