

Similar photo

Orto ORTO-T ... MR

ORTO-T 9500-840 MR

Tablelamp with direct-indirect beam, luminaire head in extruded aluminium, arranged longitudinally to the stand with precision 90° die-cast component, white (similar to RAL9016), powder-coated.

Pre-fitted cell-shaped louvre MR in vapour-coated matte polycarbonate for optical control of direct light distribution. Optical controllers indirect through cover, clear panel.

Mounted on table using clamp stand; clamp width: 15 mm to 40 mm.

Black mains cable with Schuko plug, 3 m in length. Touchpanel for switching and dimming installed in the stand and integrated USB charging station.


Mid-power LED modules for maximum lighting efficiency.

Colour rendering in index Ra > 80, colour temperature 4000 Kelvin (-840).

Protection class I, protection rating IP20.

Non-standard designs with smooth, polished powder coating, only available in combination with matte brushed nickel or polished chrome corner connector, end cap and stand adapter.

Lamps	Ballast	Prod. code
1xLED 33 W / 1xLED 40 W	LED Driver DALI	SPG0630029AH



Dimens. [mm]			Weight [kg]			
L	B	H				
1314	62	1460	7,3			

EEC A++ - A

Energy efficiency class scale A++ - E

Orto
ORTO-T ... MR