



Pergament Round LED surface-mounted ceiling luminaire small

Design C. Meyer, M. Kocks, P. H. Neuhorst

PERGA-RA 310/1900/840 AQ

Round luminaire element comprising an acrylic glass block with transparent superpolished exterior. Underneath painted matt to reduce glare. Luminaire element integrated in an outer steel powder-coated sectional aluminium cylindrical frame. The acrylic block is scratchproof and insensitive to fingerprints, and is connected to a poweder-coated metal body by a bayonet and snap fastening. The metal body accommodates the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for installation or exchange using a key-hole screw connection. Electrical connection of the flat LED board by means of a plug. Luminaire with heat-resistant wiring. Homogenous illumination of the light surface. Suitable for ceiling or wall mounting. Light colours 830 or 840. Also in a dimmable version.

Protection rating IP20, safety class I.


Colour


Metal body – similar to RAL 9016 white silk matt Frame – white (WS), silver (SI), black (AQ)

Lamps	Ballast	Prod. code	
1xLED-M 10W	LED Driver	SPP0000196	
Luminaire luminous	Luminaire output	Luminaire efficiency	
(1 []]	F14/7	FI (1417)	

 flux [Im]
 [W]
 [Im/W]

 1188
 14
 84





Dimens. [mm]		Weight	Photometric data				
	Н	D	[kg]		Longitudinal UGR	TransverseUGR	LOR
	98	310	8,4		21.6	21.5	62.5 %



Pergament
Round LED surface-mounted ceiling
luminaire small

