

Stora Rectangular LED surface-mounted luminaire MPS



STORA-PA-LED 5200/840 MPS-DA


Rectangular luminaire element with microprism panel mounted in a profile frame made of power-coated aluminium. The frame is screwed to the powder-coated metal gear tray body. The underneath of the metal body accommodates the LED module formed as a rectangular LED flat board, the top houses the electrical components. The indirect lighting component is provided by recesses in the top of the metal body. Mechanical ceiling fixture to a white powder-coated mounting box takes place using a connecting spring, electrical connection by means of a plug and socket system. The luminaire is configured with heat-resistant wiring. Variant suitable for office workplaces with microprism panel MPS. The LED spots are visible as circles on the microprism panel. Suitable for ceiling or wall mounting. Light colours 4000 K (840) or 3000 K (830). Also in a dimmable version.

Protection rating IP20, safety class I.

Colour:

Frame – similar to RAL 9016 white silk matt

Lamps	Ballast	Prod. code
2xLED-M 16 W	LED Driver DALI	SPC0630004



Dimens. [mm]				Weight [kg]			
L	B	H					
1070	330	85		13,5			

EEC A++ - A

Energy efficiency class scale A++ - E

Stora
Rectangular LED surface-mounted
luminaire MPS

