

Stora Round LED surface-mounted luminaire



STORA-RA-LED 4300/840 OS



Round luminaire element with an opal acrylic panel mounted in a profile frame made of power-coated aluminium. The frame is fastened on the powder-coated steel body using a bayonet catch with spring clip. The steel body houses the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. The luminaire is configured with heat-resistant wiring. Homogeneous illumination of the light surface. Suitable for ceiling or wall mounting. Light colour 4000 K. Also in a dimmable version.

Protection rating IP20, safety class I.

Colour:

Frame - similar to RAL 9016 white silk matt

Lamps	Ballast	Prod. code
1xLED-M 27 W	LED Driver	SPC0620006
Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
3600	31	116



Dimens. [mm]			Weight [kg]	Photometric data		
L	B	H		Longitudinal UGR	Transverse UGR	LOR
420	420	77	4,5	26,5	25,9	100,0 %

EEC A++ - A

Energy efficiency class scale A++ - E

Stora **Round LED surface-mounted luminaire**

