

Stora Round LED surface-mounted luminaire MPS



STORA-RA-LED 4300/840 MPS-DA

Round luminaire element with a microprism panel mounted in a profile frame made of power-coated aluminium. The frame is fastened on the powder-coated steel body using a bayonet catch with spring clip. The steel body houses the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. The luminaire is configured with heat-resistant wiring. Variant suitable for office workplaces with microprism panel MPS. The LED spots are visible as circles on the microprism panel. Suitable for ceiling or wall mounting. Dimmable.


Protection rating IP20, safety class I.


Colour:

Frame - similar to RAL 9016 white silk matt

Lamps	Ballast	Prod. code		
1xLED-M 27 W	LED Driver DALI	SPC0630031		

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [Im/W]	
3119	31	100	





Dimens. [mm]		Weight		Photometric data			
L	В	н	[kg]		Longitudinal UGR	TransverseUGR	LOR
420	420	77	4,3		19.9	19.1	99.8 %

EEC A++ - A

Energy efficiency class scale A++ - E



Stora
Round LED surface-mounted luminaire
MPS

