



Stora Round LED pendant luminaire

STORA-RP-LED 4300/840 OS

Round luminaire element with an opal acrylic panel mounted in a profile frame made of power-coated aluminium. The frame is fastened on the powder-coated steel body using a bayonet catch with spring clip. The luminaire is suspended by four trapezoidal wire pendants with ceiling fixture and transparent connecting cable with round ceiling junction box. The cable length can be adjusted at the ceiling junction box, the steel wire can be steplessly height adjusted. The steel body houses the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. The luminaire is configured with heat-resistant wiring. Homogeneous illumination of the light surface. Light colour 4000 K (840). Also in a dimmable version.



Protection rating IP20, safety class I.

Colour:

Frame - similar to RAL 9016 white silk matt

Lamps	Ballast	Prod. code
1xLED-M 27 W	LED Driver	SPC0620009

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
3900	31	125



Dimens. [mm]			Weight [kg]	Photometric data		
L	B	H		Longitudinal UGR	Transverse UGR	LOR
420	420	76	4,5	26.6	26.0	100.0 %

EEC A++ - A

Energy efficiency class scale A++ - E

Stora Round LED pendant luminaire

