



## Stora Round LED pendant luminaire MPS

### STORA-RP-LED 4300/840 MPS-DA

Round luminaire element with a microprism panel mounted in a profile frame made of power-coated aluminium. The frame is fastened on the powder-coated steel body using a bayonet catch with spring clip. The luminaire is suspended by four trapezoidal wire pendants with ceiling fixture and transparent connecting cable with round ceiling junction box. The cable length can be adjusted at the ceiling junction box, the steel wire can be steplessly height adjusted. The steel body houses the electrical components and electronic ballast. The LED module is formed as a round LED flat board and can be removed for mounting or exchange using a keyhole screw connection. Plug-in electrical connection of the LED flat board. The luminaire is configured with heat-resistant wiring. Variant suitable for office workplaces with microprism panel MPS. The LED spots are visible as circles on the microprism panel. Light colour 4000 K (840), dimmable.

Protection rating IP20, safety class I.

Colour:

Frame - similar to RAL 9016 white silk matt

#### Lamps


1xLED-M 27 W

#### Ballast

LED Driver DALI

#### Prod. code

SPC0630032



Dimens. [mm]			Weight [kg]			
L	B	H				
420	420	77	4,3			

#### EEC A++ - A

Energy efficiency class scale A++ - E

## **Stora** **Round LED pendant luminaire MPS**

